

# PRODUCT DATA SHEET



## A5200W ACRIBOND TAPE

### Double Sided Acrylic Foam

#### Product Features:

- \* Very high strength long lasting acrylic pressure sensitive adhesive.
  - \* High strength cellular foam conforms readily to irregular or curved surfaces.
  - \* Superior adhesion to stainless steel, painted steel and most plastics.
  - \* Ideal for fixing exterior wall cladding and composite panels.
  - \* Mounting and joining to replace mechanical fasteners.
  - \* Ideal for mounting car body side mouldings and badges.
  - \* Excellent UV, solvent and weather resistance.
  - \* Permanent fixing of signs and nameplates.
  - \* Shock and vibration absorption.
  - \* Good low temperature flexibility.
  - \* Gasketing and sealing.
- \* Approvals available.

#### Product Specifications:

* Adhesive:	Acrylic
* Carrier:	Acrylic foam
* Colour:	White
* Thickness:	2.0mm +/- 50um
* Liner:	Red PE
* Density:	800kg per cu. m. +/- 100kg
* Tensile strength:	7,500gf per sq. cm.
* Shear strength:	6,500gf per sq.cm. (after 24 hours)
* Peel strength:	3,200gf per 25mm (180 deg.)
* Temperature resistance:	160 deg. C (short term) 100 deg. C (long term)
* Maximum width:	400mm
* Roll length:	16.5m

**NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.