

PRODUCT DATA SHEET



A6080G ACRIBOND TAPE

Double Sided Acrylic Foam

Product Features:

- * Very high strength long lasting acrylic pressure sensitive adhesive.
- * High strength cellular foam conforms readily to irregular or curved surfaces.
- * Superior adhesion to stainless steel, painted steel and most plastics.
- * Mounting and joining to replace mechanical fasteners.
- * Ideal for mounting car body side mouldings and badges.
- * Excellent UV, solvent and weather resistance.
- * Permanent fixing of signs and nameplates.
- * Shock and vibration absorption.
- * Good low temperature flexibility.
- * Gasketing and sealing.

Product Specifications:

* Adhesive:	Acrylic
* Carrier:	Acrylic foam
* Colour:	Grey
* Thickness:	0.80mm +/- 50um
* Liner:	Red PE
* Density:	800kg per cu. m. +/- 100kg
* Tensile strength:	6,500gf per sq. cm.
* Shear strength:	6,500gf per sq.cm. (after 24 hours)
* Peel strength:	3,700gf per 25mm (180 deg.)
* Temperature resistance:	160 deg. C (short term) 100 deg. C (long term)
* Maximum width:	400mm
* Roll length:	66m

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.

MP250908