

# PRODUCT DATA SHEET



## 132 JOIST PROTECTION TAPE UV Stabilised Woven Polyethylene Film

### Product Features:

- \* Strong adhesion to timber, metal and most plastics.
- \* Excellent UV protection.
- \* Exhibits excellent properties for aging and weathering.
- \* Air and waterproof seal.
- \* Hand tearable, easy to use, saves time.
- \* No liner to remove, saves time and money and waste.

### Applications:

- \* Suitable for protection of timber joists and bearers.
- \* Sealing around windows and doors.
- \* General purpose exterior joining and repairs.
- \* Repair or reinforce greenhouses and tunnel houses.
- \* Maintain and repair agricultural films.
- \* Waterproofing and sealing.

### Product Specifications:

* Adhesive:	Solvent based acrylic
* Backing:	Polyethylene, polyethylene cloth
* Total thickness:	0.170mm
* Colour:	Black
* Tensile strength:	48N per 10mm
* Adhesion to steel:	7N per 10mm
* Temperature resistance:	90 deg. C.
* UV resistance:	Excellent
* Elongation:	9%

**NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.